

Performance	ENGLISH	SI	
Measurement Range(for ±5V output)	10,000 psi	68,950 kPa	
Sensitivity(± 15 %)	0.5 mV/psi	0.07 mV/kPa	
Maximum Pressure	15,000 psi	103,420 kPa	
Resolution	0.2 psi	1.379 kPa	[1]
Resonant Frequency	≥ 25 kHz	≥ 25 kHz	[2]
Rise Time	≤ 20 μ sec	≤ 20 μ sec	[2]
Low Frequency Response(- 5 %)	0.0005 Hz	0.0005 Hz	
Non-Linearity	≤ 1.0 % FS	≤ 1.0 % FS	[3]
<b>Environmental</b>			
Acceleration Sensitivity	≤ 0.002 psi/g	≤ 0.0014 kPa/(m/s <sup>2</sup> )	[4]
Temperature Range(Operating)	-100 to +250 °F	-73 to +121 °C	
Temperature Coefficient of Sensitivity	≤ 0.03 %/°F	≤ 0.054 %/°C	
Maximum Flash Temperature	10,000 °F	5,538 °C	
Maximum Vibration	2,000 g pk	19,600 m/s <sup>2</sup> pk	
Maximum Shock	10,000 g pk	98,070 m/s <sup>2</sup> pk	
<b>Electrical</b>			
Output Polarity(Positive Pressure)	Positive	Positive	
Discharge Time Constant(at room temp)	≥ 1,000 sec	≥ 1,000 sec	
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 Ohm	≤ 100 Ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
<b>Physical</b>			
Housing Material	17-4 Stainless Steel	17-4 Stainless Steel	
Diaphragm	Invar	Invar	
Sealing	Hermetic	Hermetic	
Electrical Connector	Integral Cable	Integral Cable	
Weight	4.59 oz	130 gm	
Helium Flow Rate(at 1,500 psi)	40 scf/hr	1.13 m <sup>3</sup> /hr	
Water Flow Rate(at 50 psi)	1.2 gal/min	4.5 L/min	
Cable Length	4 ft	1.2 m	

**OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

**NOTES:**

[1]Typical.  
 [2]With helium flow.  
 [3]Zero-based, least-squares, straight line method.  
 [4]Applies to internal amplifier, not to external housing.  
 [5]See PCB Declaration of Conformance PS023 for details.

**SUPPLIED ACCESSORIES:**

Model 065A15 Seal, .624" OD x .553" ID x .080", brass (3)  
 Model 065A72 Water cooling tubes (o-ring sealed) (2)  
 Model 070A08 Cable adaptor (micro 10-32 jack to BNC jack) (1)

Entered: ND	Engineer: RPF	Sales: RWM	Approved: RPF	Spec Number:
Date: 01/11/2024	Date: 01/11/2024	Date: 01/11/2024	Date: 01/11/2024	68595

**PCB PIEZOTRONICS**  
 AN AMPHENOL COMPANY

Phone: 716-684-0001  
 Fax: 716-684-0987  
 E-Mail: info@pcb.com

3425 Walden Avenue, Depew, NY 14043



All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.  
 ICP® is a registered trademark of PCB Piezotronics, Inc.